

EVAPOR-RUST

PROLAN

High Performance Lanolin Lubricant

ENDURO MEDIUM GRADE

Benefits:

- After 24hrs this forms an outer skin that is not tacky and leaves a shiny finish.
- Will not collect dust after outer skin has formed
- Biodegradable
- Non-Carcinogenic
- Non-Leaching
- Non-evaporative
- Non-conductive to 70kv
- Penetrates into surface rust
- Penetrates into grooves and joints
- Resists acids and salts
- Hermetically seals off surfaces
- Cold water blasting won't remove
- Won't break down rubber and wiring



Light brown medium thickness liquid that is easily sprayable.
Leaves a clean shiny finish overnight

Available in Sizes:

5 Litre, 20 Litre, 200 Litre

Applications:

- For Corrosion protection
- Frame protection on ATV Vehicle chassis, 4WD's, Tractors, Quad Bikes on dairy farms or in the surf
- Rust preventative on equipment being shipped Overseas
- Spare Parts in Storage
- General workshop lubricant for boats, motors, engines, covers and trailers showing signs of rust and corrosion .
- Protection for horticultural equipment and parts.

Physical Properties:

- State; Liquid-light brown colour
- Insoluble in water
- Relative vapour density (air=1): 5.3
- Lower explosive limit (%): 1.0
- Upper explosive limit (%): 6.0
- Auto-ignition Temp (°C): 227
- Boiling range(°C): 110-200
- Specific Gravity (water=1):0.81-0.83 @24°C
- Vapour Pressure (kPa): 0.4 @ 38°C
- Evaporation rate: 0.05 (BuAc=1)
- Flash Point (°C): 66
- Viscosity (B-Viscos): 15.0
- Non conductive point: 70Kv
- Dispose of rags away from ignitable materials

Contents:

Lanolin, blended with non-regulated, paraffin carriers and natural oils to reduce tackiness and make application simple.

Evapo-Rust Pty Ltd

Email: sales@evapo-rust.com.au, Phone: +64 9 424 1792 or 0408 726 304

www.evapo-rust.com.au